



Actualize your creativity
into colours and shapes!

Pixy T2

60cm DTF Textile Solution with 2 heads



2xEpson I3200 A1
Natural 600dpi



White Ink Circulation



THK Quiet Guide



Ink Shortage Alarm

60CM Direct to Film Printer


| ITEM | SPECIFICATION | | |
|-------------------------|---|-------------|----------|
| Model | Pixy T2 | | |
| Print Head | 2x Epson I3200 A1 Print Heads | | |
| Resolution | Mode | Resolution | Output |
| | 4pass | 720x1200dpi | 15 sqm/h |
| | 6pass | 720x1800dpi | 10 sqm/h |
| Ink | GS Orignal Transfer Pigment Ink | | |
| Color Configuration | 1xKCMY+1xW | | |
| Ink Supply System | Bulk Ink Supply System with White Ink Circulation System | | |
| Ink Tank | 1500ml | | |
| Media Type | Transfer Film | | |
| Printing Width | 600mm | | |
| RIP Software | Onyx DTF+GZ Printer Manager | | |
| Data Interface | External: Ethernet; Internal: Fiber Optical | | |
| Power | Single phase, 50Hz/AC, 220V±10%, 2.27A, 500W | | |
| Working Environment | Temp:18°C-30°C; Humidity:35%-65% | | |
| Installed Size | LxWxH(mm) 1661×815×1507 | | |
| Printer Packed Size | LxWxH(mm) 2200×960×790 | | |
| Net Weight/Gross Weight | 170KGS/240KGS | | |
| SHAKER & FILTER | | | |
| Heating & Drying System | Four Rows High-Efficient Drying Lamp & Cold Air Fan Drying | | |
| Power | Single phase, 50Hz/AC, 220V±10%, 23A(Shaker)+2A(filter) ; Shaker: 5000W; Filter: 440W | | |
| Installed Size | Shaker: LxWxH(mm) 2614x1022x1092; Filter: LxWxH(mm) 530x571x1366 | | |
| Packed Size | Shaker: L×W×H(mm) 1800×1130×1130; Filter: L×W×H(mm) 680×630×1540 | | |
| Net Weight/Gross Weight | Shaker: 182KGS/288KGS; Filter: 95KGS/122KGS | | |

*Specifications are liable to change without prior notice.



High Standard Motion System

Anti-deformation structure supported by aluminum beam. The highly acclaimed Icus chain and imported high-precision THK linear guide ensure stable and low noise movement.



Active Tension Bar

Active tension bar with constant tension and fixed movement range ensure wrinkle free printing and precise stepping. Enhanced structure of platform prevent deformation during transportation.




User-Friendly Design

Built-in LED lights help operator check printing quality and maintain easily. Buttons, rotary knobs and real-time data displays installed in the front of the machine ensure convenient operation and improve operator's experience.



Touch-Screen Panel

User friendly touch screen panel and electric driven pinch roller installed in the front and rear of the printer ensure smooth and convenient operation, enhancing user's experience and improving work efficiency.



White Ink Recirculation System

The white ink is circulated at regular intervals during idle time to prevent pigment sedimentation that leads to malfunctions of the print head. Specially designed rotary unit prevents idle white ink bottle sedimentation.



Convenient Moisturizing System

Built-in bottle of flush for white heads allows one week free of maintenance after moisturizing, with module inside the software ensures convenient operation, intensively prolong the life of print heads.

Gongzheng Group Co., Ltd.

Address: Miaobei Village, Yongjia County, Wenzhou City, Zhejiang Province, China 325102
Tel: +86-577-67319778
Email: gzsales@gongzheng.com
Web: www.gongzheng.com

Ver 2025.01.07



Authorized distributor: