

DTF-A30 V2

DIRECT TO FILM PRINTER



Self-development



long life




High precision



low cost

TECHNICAL PARAMETER

Model	DTF-A30 V2		
Printhead	2/3*Epson I1 600-A1		
Printing Color	4C+W or 6C+W(Lc/Lm/Fo/Fg as option)		
Printing Speed	High speed mode	720*900DPI 6PASS 5m²/h 720*1200DPI 8PASS 4m²/h 720*1800DPI 12PASS 3m²/h	960*900DPI 6PASS 4m²/h 960*1200DPI 8PASS 3m²/h 960*1800DPI 12PASS 2m²/h
	High precision mode	720*900DPI 6PASS 4m²/h 720*1200DPI 8PASS 3m²/h 720*1800DPI 12PASS 2m²/h	960*900DPI 6PASS 3m²/h 960*1200DPI 8PASS 2m²/h 960*1800DPI 12PASS 1m²/h
Printing Size	300mm		
RIP Software	RIIN/Flexiprint/CADlink/Maintop/NeoStampa		
Media Transfer	Auto feeding and take-up system		
Heating Method	Front and back independent heating		
Ink System	Auto ink supply,white ink circulating and stirring		
Power Supply	110V/220V 50~60HZ 230W/1500W		
Work Environment	Temperature:20°C~30°C Humidity:35%~65%		
Machine Size/Weight	Printer:1180*852*1256mm 105kg Powder Shaker:640*932*577mm 45kg		
Packaging Size/Weight	Printer:1570*880*740mm 123kg Powder Shaker:800*600*720mm 56kg		




High precision guide rail



Paper-lack sensor



Ink shortage alarming



White stir and circulate