

UV-F30

UV DTF PRINTER



Self-development



long life



High precision



low cost

TECHNICAL PARAMETER

Model	UV-F30		
Printhead	2*Epson F1080		
Printing Color	CMYK+W+V		
Printing Size	300mm		
Printing Speed	CMYK+White solution	High speed mode	360*1440DPI 8PASS 1.7m²/h 360*2160DPI 12PASS 1.1m²/h
		High precision mode	360*1080DPI 6PASS 1.9m²/h 360*1440DPI 8PASS 1.6m²/h 360*2160DPI 12PASS 0.9m²/h
	color+white+color solution	High speed mode	360*1440DPI 8PASS 1.1m²/h 360*2160DPI 12PASS 0.9m²/h
		High precision mode	360*1080DPI 6PASS 1.3m²/h 360*1440DPI 8PASS 0.9m²/h 360*2160DPI 12PASS 0.7m²/h
RIP Software	RIIN/Flexiprint/CADlink/Maintop/NeoStampa		
Media Transfer	UV AB film		
Lamination	Integrated automatic laminator		
Cooling	Air cooling		
Power Supply	220V 50~60HZ 300W		
Work Environment	Temperature:20°C~30°C Humidity:35%-65%		
Machine Size/Weight	910*949*1078mm 100kg		
Packaging Size/Weight	1220*750*650mm 116kg		




CMYK+W+V



Varnish stirring



HIWIN guide rail



Air cooling